

# FEATURES

Compaq ProLiant 5500R

## Compaq ProLiant 5500R 6/200

### System Unit

Microprocessor	200-MHz Intel Pentium® Pro processor
Upgradability	Upgradable to quad processing
Cache	512-KB level 2 writeback protected cache per processor
Processor Sockets	4
Expansion Slots	
I/O (Total)	8, 7 available
PCI	5
Shared PCI/EISA	3
RAM	
Standard	128 MB
Maximum	3 GB

### Network Interface Controllers

Netelligent 100 FDDI PCI SAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS UTP	Optional
Netelligent 100 FDDI PCI DAS UTP	Optional
Netelligent 100 FDDI EISA SAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA DAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA SAS UTP	Optional
Netelligent 100 FDDI EISA DAS UTP	Optional
Netelligent 10/100 TX PCI UTP	Standard
Netelligent 10 T/2 PCI UTP/Coax	Optional
Netelligent 10 T/2 ISA UTP/Coax	Optional
Netelligent 10 T PCI UTP	Optional
Netelligent 16/4 TR PCI IBM UTP/STP	Optional
Netelligent 4/16 TR PCI UTP/STP	Optional
Netelligent Dual 10/100 TX PCI UTP	Optional
NetFlex-3/P	
100 Base-TX Upgrade Module	Optional (for NetFlex-3)
100Base-FX Upgrade Module	Optional (for NetFlex-3)
100VG-AnyLAN Upgrade Module	Optional (for NetFlex-3)

**Compaq ProLiant 5500R 6/200**
**Server Management**

Compaq Insight Manager	Standard
Integrated Remote Console	Standard
Integrated Management Display	Standard
Automatic Server Recovery	Standard
Server Health Logs	Standard
Recovery Server Option	Optional
Compaq Remote Insight Board	Optional

**Storage**

Diskette Drives	1.44-MB
CD-ROM Drives	
Standard	16X Max <sup>1</sup> CD-ROM IDE
Optional	IDE or SCSI
Hard Drives <sup>2</sup>	
Standard	None
Optional	2.1-GB, 4.3-GB, 9.1-GB Wide-Ultra SCSI-3 Drives 2.1-GB, 4.3-GB, 9.1-GB, 18.2-GB Pluggable Wide-Ultra SCSI-3 Drives 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Drives
External Storage	
Rack-mountable ProLiant Storage System Models /F1 and /F2 ProLiant Storage System Models /U1 and /U2	Optional
Rack-mountable SCSI Storage Expander	Optional
CD-Storage System	
Rack Model	Optional
Maximum Storage Capacity	
Internal	127.4 GB (6 x 1.6-inch hot-plug internal hard drives) using 18.2-GB hard drives; 2 x 9.1-GB hard drives installed into available removable media bays
External	1.5 TB (12 ProLiant Storage Systems each with 7 x 18.2-GB hard drives)
Total	1.7 TB
Tape Drives	
Optional	2/4-GB DAT, 4/8-GB DAT, TurboDAT AutoLoaders, 15/30-GB DLT, 35/70-GB DLT, DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Model 3570-1, DLT 15 Cartridge Library Model 3570-2
Controllers	
Standard	Integrated Dual Channel Wide-Ultra SCSI-3
Optional	Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, SMART 2/E Array

**Compaq ProLiant 5500R 6/200**
**Interfaces**

Parallel	1
Serial	2
Pointing Device (mouse)	1
Graphics	1
Keyboard	1
External Fast-Wide SCSI-2	1
Network RJ-45	1

**Graphics**

Integrated 1024 x 768 by 256 color, 1 MB noninterlaced Video System	Standard
--	----------

**Monitors**

V55 Color	Optional
V75 Color	Optional
P50 Color	Optional
P75 Color	Optional

**LCD Displays**

Integrated Management Display	Standard
-------------------------------	----------

**Keyboard**

Keyboard and Mouse	Optional
--------------------	----------

**Supported System Software  
from Compaq**

Compaq Insight Manager	Standard
Compaq SmartStart	Standard
Microsoft Windows NT Server 3.51 and 4.x	Optional
Novell intraNetWare	Optional
Novell intraNetWare For Small Business	Optional
Novell intraNetWare SFT-III	Optional
Novell intraNetWare SMP	Optional
Novell NetWare 3.20 and 4.10	Optional
IBM OS/2 2.x	Optional
IBM OS/2 Warp Family of Products	Optional
SCO OpenServer 5	Optional
SCO UnixWare 2.1	Optional
Solaris X86 2.5.x and 2.6	Optional

<sup>1</sup> Data transfer rate will vary from 150 KB/s to 2400 KB/s.

<sup>2</sup> Hard drive specifications may vary slightly depending on vendor.